



## MODEL NUMBER AND OPTIONS

Triboflow 2200 - **1** [ ] [ ] [ ] [ ] [ ] - [ ] [ ] [ ] [ ] [ ] [ ]

### ELECTRONICS

**EI Relay Contacts** \_\_\_\_\_  
 1. 5 Amp DPDT - Standard  
 9. Special

**EII Power Requirement** \_\_\_\_\_  
 1. 120 VAC - Standard  
 2. 240 VAC - Add  
 3. 10-32 VDC - Add  
 9. Special

**EIII Enclosure** \_\_\_\_\_  
 1. NEMA 12 - Standard  
 2. NEMA 4 - Add  
 3. NEMA 7/9 (Explosion Proof) - Add  
 4. NEMA 4x S.S. - Add  
 9. Special

**EIV Options** \_\_\_\_\_  
 1. None  
 2. Pulse Feed Circuit - Standard  
 9. Special

### SENSOR

**SI Probe Material** \_\_\_\_\_  
 1. 316 Stainless Steel - Standard  
 2. Tungsten Carbide (Abrasion Resistant) - Add  
 9. Special

**SII Fitting/Insulation** \_\_\_\_\_  
 1. Teflon - Standard  
 2. High Temperature & Pressure/Ceramic - Add  
 3. Teflon with Air Purge - Add  
 4. High Temperature & Pressure/Ceramic with Air Purge - Add  
 5. Extended High Performance - Add  
 6. Extended High Performance with Air Purge - Add  
 9. Special

**SIII Probe Insertion Length \*** \_\_\_\_\_  
 1. 1/2 in (1.3 cm) - Std      5. 18 in (45.7 cm) - Add  
 2. 3 in (7.6 cm) - Add      6. 30 in (76.2 cm) - Add  
 3. 6 in (15.2 cm) - Add      7. 36 in (91.4 cm) - Add  
 4. 12 in (30.5 cm) - Add      9. Special

**SIV Sensor Mounting** \_\_\_\_\_  
 Q. Quick Release - Standard  
 N. 1/2 in NPT - Standard  
 S. Special

**Cable Length** \_\_\_\_\_  
 Total Length \_\_\_\_\_ ft. @\$ \_\_\_\_\_ /ft

**Connectors** \_\_\_\_\_  
 Factory Installed \$ \_\_\_\_\_ Set  
 Field Kits \$ \_\_\_\_\_ Set

\*Probe should reach approximately mid-duct.

**UNIT PRICE \$** \_\_\_\_\_

### EXTRAS

Manuals (one included) # \_\_\_\_\_ @\$ \_\_\_\_\_ ea.  
 Stainless Steel Tags # \_\_\_\_\_ @\$ \_\_\_\_\_ ea.  
 Set of Sepias # \_\_\_\_\_ @\$ \_\_\_\_\_ ea.  
 Set of Prints # \_\_\_\_\_ @\$ \_\_\_\_\_ ea.  
 Spare Parts Kit # \_\_\_\_\_ @\$ \_\_\_\_\_ ea.  
 Field Test Unit # \_\_\_\_\_ @\$ \_\_\_\_\_ ea.

**Extras Total \$** \_\_\_\_\_

## PRICE AND ORDER INFORMATION **Model 2200-1**

### CUSTOMER

Individual \_\_\_\_\_  
 Title \_\_\_\_\_  
 Company \_\_\_\_\_  
 Address \_\_\_\_\_  
 \_\_\_\_\_  
 City, State, Zip \_\_\_\_\_  
 Phone # ( ) \_\_\_\_\_  
 Fax # ( ) \_\_\_\_\_

### PROCESS CONDITIONS

Temperature \_\_\_\_\_ °F(°C)      Pressure \_\_\_\_\_ psig(bar)  
 Duct ID \_\_\_\_\_ inches(cm)      Velocity \_\_\_\_\_ f/s(m/s)  
 Solid \_\_\_\_\_      Gas \_\_\_\_\_  
 Comments \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### APPLICATION

Flow Control       Bin Bridging  
 Flow/Feed Loss       Screw Feeder Blockage  
 Pneumatic Conveyor Blockage       Cyclone Overflow  
 Additive Blending  
 Other \_\_\_\_\_ (please specify)

P.O. # \_\_\_\_\_

**Model Number 2200 -** **1** [ ] [ ] [ ] [ ] [ ] - [ ] [ ] [ ] [ ] [ ] [ ]

Unit Price \$ \_\_\_\_\_ # Units \_\_\_\_\_

Extras \$ \_\_\_\_\_ **Total \$** \_\_\_\_\_

Delivery \_\_\_\_\_ Days ARO  
Terms net 30 days; FOB Danvers, MA

Quotation # \_\_\_\_\_ Date \_\_\_\_\_  
 Prices remain as quoted for 30 days

Signature \_\_\_\_\_

### REPRESENTED BY

### Auburn International, Inc.

Danvers Industrial Park  
 Eight Electronics Avenue  
 P.O. Box 2008  
 Danvers, MA 01923

Phone: (508) 777-2460  
 (800) 255-5008  
 FAX: (508) 777-8820